according to Regulation (EC) No. 1907/2006

# PRECISION TM SYNTHETIC MOLY (WYMARK GREASE EPM)



### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PRECISION ™ SYNTHETIC MOLY (WYMARK GREASE EPM)

Product code : PSMKGL, PSMDRL, PSMCBG, PSM, PSMC30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : PRECISION SYNTHETIC MOLY is a synthetic, high Substance/Mixture performance, all season EP grease with long life and

improved low temperature properties where shock loading

conditions are encountered.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way

Birmingham International Park Solihull B37 7HB

United Kingdom

E-mail address of person

responsible for the SDS

: EUSDS@suncor.com

1.4 Emergency telephone number

Emergency telephone

number

Suncor Energy: +1 403-296-3000;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

**SECTION 2: Hazards identification** 

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting

effects.

Classification (67/548/EEC, 1999/45/EC)

Dangerous for the environment R52/53: Harmful to aquatic organisms, may cause

long-term adverse effects in the aquatic

environment.

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY



Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

> P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

### 2.3 Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

# **Hazardous components**

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Benzene, polypropene derivs.	68081-77-6		Asp. Tox. 1; H304 Aquatic Chronic 4; H413	20 - 25
Benzene, mono-C10- 13-alkyl derivs., distn. residues	84961-70-6 284-660-7		Asp. Tox. 1; H304	20 - 30
Benzene, C14-30-alkyl derivs.	68855-24-3 272-472-8		Asp. Tox. 1;	20 - 30
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1 270-128-1	R52/53	Aquatic Chronic 3; H412	2.5 - 10
bis(nonylphenyl)amine	36878-20-3 253-249-4	R53	Aquatic Chronic 4; H413	1 - 2.5
Phenol, isobutylenated, phosphate (3:1)	68937-40-6 273-065-8	N; R50/53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.25 - 1
triphenyl phosphate	115-86-6 204-112-2	N; R50/53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.1 - 0.25



# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY





For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

> Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

### 4.3 Indication of any immediate medical attention and special treatment needed

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during : Cool closed containers exposed to fire with water spray.

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

Page: 3 / 11 TM Trademark of Suncor Energy Inc. Used under licence.



# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY

### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

firefighting

Hazardous combustion

products

: Carbon oxides (CO, CO2), nitrogen oxides (NOx), phosphorus oxides (POx), hydrogen sulfide (H2S), ammonia, smoke and irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

> Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

### 6.2 Environmental precautions

**Environmental precautions** : Do not allow uncontrolled discharge of product into the

environment.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.

> Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### 6.4 Reference to other sections

For personal protection see section 8.

### SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY



### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against

fire and explosion

: None known.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use. Wash face, hands and any

exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

### 7.3 Specific end use(s)

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

# 8.2 Exposure controls

#### **Engineering measures**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

: Wear face-shield and protective suit for abnormal processing Eye protection

problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Chemical-resistant, impervious gloves complying with an Remarks

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

: Choose body protection in relation to its type, to the Skin and body protection

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY





### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

No special protective equipment required.

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

: Buttery, smooth, semi-solid **Appearance** 

Colour : grey

Odour : Mild grease like. Odour Threshold : No data available рH : No data available

Pour point : -54 °C (-65 °F)Base Fluid Blend

Boiling point/boiling range : No data available Flash point : 187 °C (369 °F)

> Method: Cleveland open cup Remarks: Base Fluid Blend

Fire Point : 203 °C (397 °F)

Base Fluid Blend

**Auto-Ignition Temperature** : No data available

**Evaporation rate** : No data available

: Low fire hazard. This material must be heated before ignition Flammability (solid, gas)

will occur.

Upper explosion limit : No data available Lower explosion limit : No data available Vapour pressure : No data available Relative vapour density : No data available

: 0.9098 kg/l (15 °C / 59 °F) Density

Solubility(ies)

: insoluble Water solubility

Partition coefficient: n-

octanol/water

: No data available

Viscosity

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY



### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

: 129.8 cSt (40 °C / 104 °F) Viscosity, kinematic

Base Fluid Blend

15.6 cSt (100 °C / 212 °F)

Base Fluid Blend

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

# 10.2 Chemical stability

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, reducing agents, acids, alkalis

and acidic clay.

# 10.6 Hazardous decomposition products

Hazardous decomposition

products

May release COx, NOx, SOx, POx, H2S, MoOx, metal oxides, lithium compounds, smoke and irritating vapours when heated

to decomposition.

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Information on likely routes of : Eye contact

exposure

Ingestion Inhalation

Skin contact

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Remarks: No data available

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY





: Remarks: No data available Acute inhalation toxicity

: Remarks: No data available Acute dermal toxicity

**Components:** 

Benzene, C14-30-alkyl derivs.:

Acute oral toxicity : LD50 Rat: > 15,800 mg/kg,

Acute dermal toxicity : LD50 Rabbit: > 7,940 mg/kg,

triphenyl phosphate:

Acute oral toxicity : LD50 Rat: 3,500 mg/kg,

LD50 Mouse: 1,320 mg/kg,

Acute dermal toxicity : LD50 Rabbit: > 7,900 mg/kg,

Skin corrosion/irritation

**Product:** 

Remarks: No data available

Serious eye damage/eye irritation

**Product:** 

Remarks: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available


Reproductive toxicity


No data available

STOT - single exposure

No data available

STOT - repeated exposure







# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY



Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

No data available

### **Aspiration toxicity**

No data available

# **SECTION 12: Ecological information**

### 12.1 Toxicity

**Product:** 

: Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

: Remarks: No data available Toxicity to algae

Toxicity to bacteria

Remarks: No data available

### 12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

# 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

# 12.6 Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

™ Trademark of Suncor Energy Inc. Used under licence.

Page: 9 / 11



# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY



### 000003000889

Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

# **SECTION 14: Transport information**

# International Regulation

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**49 CFR** 

Not regulated as a dangerous good

**TDG** 

Not regulated as a dangerous good

### Special precautions for user

Not applicable

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

: WGK 2 water endangering

### The components of this product are reported in the following inventories:

: On the inventory, or in compliance with the inventory **IECSC** 

DSL : On the inventory, or in compliance with the inventory

**TSCA** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

**ELINCS** : On the inventory, or in compliance with the inventory

# according to Regulation (EC) No. 1907/2006 PRECISION TM SYNTHETIC MOLY





Version 3.0 Revision Date 2015/03/26 Print Date 2015/03/26

### 15.2 Chemical Safety Assessment

### **SECTION 16: Other information**

### **Full text of R-Phrases**

R50/53 : Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

: Harmful to aquatic organisms, may cause long-term adverse R52/53

effects in the aquatic environment.

: May cause long-term adverse effects in the aquatic **R53** 

environment.

#### **Full text of H-Statements**

H304 : May be fatal if swallowed and enters airways.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects. : Harmful to aquatic life with long lasting effects. H412 H413 May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity Aquatic Chronic : Chronic aquatic toxicity : Aspiration hazard Asp. Tox.

For Copy of (M)SDS : Internet: lubricants.petro-canada.ca/msds

Europe, telephone: 00-800-7387-6000

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.